

Maelstrom Rear Discharge Spreaders

Built to a high capacity specification and capable of achieving a spread width of up to 12m (40ft), the West Rear Discharge unit is particularly suitable for farmyard manure. With the optional hydraulic rear gate, it can also be used with poultry manure and semi-solids.

The twin rear vertical rotating beaters operate at a powerful 400 rpm from the PTO drive input of 1000 rpm. For trouble free maintenance the rear beaters are fitted with replaceable blades, and feature a protected two-piece drive-line with a PTO with slip clutch.

The Rear Discharge machine has large diameter wider tyres to minimise ground pressure and is fully equipped for road use as standard with hydraulic brakes, hand brake and lighting.



Maelstrom 8



Maelstrom 10



Maelstrom 14

Standard Features

- ❖ 24mm adjusters
- ❖ LED lights
- ❖ Wide angle PTO
- ❖ Chain drive with padless connectors

Optional Equipment

- ❖ Electric hydraulic in cab controls
- ❖ Weighing system
- ❖ FYM GPS Control system
- ❖ Slurry door
- ❖ Mudguards



Spreader Specifications



24mm adjusters



Sprung drawbar standard on Maelstrom 14



LED Lights



Wide angle PTO

| | M8 | M10 | M12 | M14 | M16 | M18 |
|---------------------|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Capacity Level | 8.0m ³ | 10.0m ³ | 12.0m ³ | 14.0m ³ | 16.0m ³ | 18.0m ³ |
| Loading Height | 2.04m | 2.27m | 2.50m | 2.53m | 2.75m | 2.88m |
| Overall Length | 7.50m | 7.50m | 7.50m | 8.00m | 8.00m | 8.00m |
| Overall Height | 2.59m | 2.59m | 2.59m | 3.12m | 3.12m | 3.12m |
| Overall Width | 2.75m | 2.75m | 2.75m | 2.90m | 2.90m | 2.90m |
| Overall Weight | 4900kg | 4960kg | 5050kg | 6020kg | 6090kg | 6200kg |
| Internal Length | 4.53m | 4.53m | 4.53m | 5.30m | 5.30m | 5.30m |
| Internal Height | 0.79m | 1.00m | 1.25m | 1.24m | 1.46m | 1.60m |
| Internal Width | 1.50m | 1.50m | 1.50m | 1.50m | 1.50m | 1.50m |
| Extensions fitted | N/A | Timber | Metal | N/A | Timber | Metal |
| Side Plates | 4mm | 4mm | 4mm | 4mm | 4mm | 4mm |
| Floor Plates | 4/5mm | 4/5mm | 4/5mm | 4/5mm | 4/5mm | 4/5mm |
| Axle Beam | 130mm | 130mm | 130mm | 150mm | 150mm | 150mm |
| Brake Size | 406/120 | 406/120 | 406/120 | 406/140 | 406/140 | 406/140 |
| Tyre Size | 580/70R38 | 580/70R38 | 580/70R38 | 580/70R38 | 580/70R38 | 580/70R38 |
| Chain Size | 14mm | 14mm | 14mm | 18mm | 18mm | 18mm |
| Sprung Drawbar | No | No | No | Standard | Standard | Standard |
| PTO / Slip Clutch | Standard | Standard | Standard | Standard | Standard | Standard |
| LED Lights | Standard | Standard | Standard | Standard | Standard | Standard |
| Swivel Hitch | Optional | Optional | Optional | Standard | Standard | Standard |
| K80 Hitch | Optional | Optional | Optional | N/A | N/A | N/A |
| Slurry Door | Optional | Optional | Optional | Optional | Optional | Optional |
| Electrical Controls | Optional | Optional | Optional | Optional | Optional | Optional |
| Mudguards | Optional | Optional | Optional | Optional | Optional | Optional |



Harry West (Prees) Limited
Agricultural Engineers

Lower Heath, Prees, Whitchurch, Shropshire SY13 2BT
Telephone +44 (0)1948 840465 Fax +44 (0)1948 841055
email sales@harrywest.co.uk www.harrywest.co.uk

